

Type	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power ΔT=50K (75/65/20 °C) [W]	Power ΔT=46K (75/65/24 °C) [W]	Power ΔT=30K (55/45/20 °C) [W]	Electric heater maximum power [W]
	W	H	D	C	B								
B00055509041400D0000	555	904	65-70	50	50-55	515	0,51	6,2	3,1	292	264	158	300
B00055511201400D0000	555	1120	65-70	50	50-55	515	0,62	7,3	3,7	352	319	190	300
B00055513361400D0000	555	1336	65-70	50	50-55	515	0,72	8,5	4,2	411	372	222	300

Horizontal profiles:

Circuital profile:

Finishing and warranty:	Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty;	
Mounting brackets:	brackets in the colour of the radiator are included	
Valve:	order separately	
Heater :	order separately	
Working pressure:	8 bars	
Maximum temperature:	120 °C	
Connections:	 on request	
	– inner threads G 1/2 – air-vent plug G1/8 hidden behind	

