

Type	Width [mm]	Height [mm]	Depth from wall [mm]	Connections spacing [mm]	Connections distance from the wall [mm]	Brackets spacing [mm]	Heating surface [m ²]	Weight [kg]	Capacity [dm ³]	Power ΔT=50K (75/65/20 °C) [W]	Power ΔT=46K (75/65/24 °C) [W]	Power ΔT=30K (55/45/20 °C) [W]	Electric heater maximum power [W]
	W	H	D	C	B	A							
H0005550773023030000	555	773	60-65	515	45-50	515	0,67	7,9	2,8	324	293	174	300
H000555077302G0300000	555	773	83-88	50	54-59	515	0,67	8,0	2,8	324	293	174	300
H0005551043023030000	555	1043	60-65	515	45-50	515	0,97	11,4	3,9	440	397	233	300
H000555104302G0300000	555	1043	83-88	50	54-59	515	0,97	11,5	3,9	440	397	233	300
H0005551583023030000	555	1583	60-65	515	45-50	515	1,53	17,7	6,1	690	621	362	600
H000555158302G0300000	555	1583	83-88	50	54-59	515	1,53	17,8	6,1	690	621	362	600

Horizontal profiles:

Vertical manifolds:

Finishing and warranty:	Nanoceramic (zirconia coating) + polyester-epoxy lacquer; 5 year warranty;
Mounting brackets:	brackets in the colour of the radiator are included
Valve:	order separately
Heater :	order separately
Working pressure:	8 bars
Maximum temperature:	120 °C
Connections:	<div style="display: flex; align-items: center; gap: 20px;"> <div style="text-align: center;"> </div> <div style="text-align: center;"> </div> <div style="font-size: small;"> – inner threads G 1/2 – air-vent plug G1/8 hidden behind </div> </div>
Accessories:	order separately
Remarks:	valid for HX radiators: water inlet on the left side

